Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-233-4278

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# Body Diameter:

1.125 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.688 inches

## Mounting Bushing Length:

0.375 inches

Body Length:

#### 0.500 inches

Shaft Style:

#### Round, slotted

Actuator Type:

Single shaft

#### Nonturn Device Location:

At 3 oclock and at 9 oclock

## Nonturn Device Radius:

0.531 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

500.000 kilohms single section

## Power Dissipation Rating Per Section In Watts:

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

# Standard Taper Curve Per Section:

A single section

# **Terminal Type And Quantity:**

3 tab, solder lug

#### Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0