## NSN 5905-00-233-4303

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-233-4303 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Overall Length:** 1.813 inches **Body Diameter:** 1.188 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.500 inches

**Body Length:** 

1.062 inches

**Shaft Style:** Round, slotted

**Shaft Bearing Type:** 

Bearing

**Actuator Type:** 

Single shaft

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

0.531 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

**Mounting Method:** 

Locking bushing

**Electrical Resistance Per Section:** 

1.000 megohms 2nd section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

**Function Conformity Per Section:** 

Single section independent linearity

**Resistance Tolerance Per Section In Percent:** 

-20.0 to 20.0 2nd section

## NSN 5905-00-233-4303

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0