## NSN 5905-00-233-4490

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-233-4490

| Section Quantity:   |  |  |  |  |  |
|---|--|--|--|--|--|
| 1   |  |  |  |  |  |
|   |  |  |  |  |  |
| Body Style:   |  |  |  |  |  |
| Rectangular w/pointer adjustment  |  |  |  |  |  |
| Reliability Indicator:  |  |  |  |  |  |
| Not established   |  |  |  |  |  |
| Terminal Length:  |  |  |  |  |  |
| 2.000 inches  |  |  |  |  |  |
| Body Length:  |  |  |  |  |  |
| 0.100 inches  |  |  |  |  |  |
| Body Width:   |  |  |  |  |  |
| 0.438 inches  |  |  |  |  |  |
| Body Height:  |  |  |  |  |  |
| 0.406 inches  |  |  |  |  |  |
| Actuator Type:  |  |  |  |  |  |
| Flush drive with slot-hole  |  |  |  |  |  |
| Center To Center Distance Between Terminals:                                |  |  |  |  |  |
| 0.312 inches  |  |  |  |  |  |
| Terminal Location:  |  |  |  |  |  |
| Lower adjacent side single row  |  |  |  |  |  |
| Mounting Method:  |  |  |  |  |  |
| Terminal  |  |  |  |  |  |
| Features Provided:  |  |  |  |  |  |
| Nonmetallic shaft   |  |  |  |  |  |
| Electrical Resistance Per Section:  |  |  |  |  |  |
| 750.0 ohms single section   |  |  |  |  |  |
| Center To Center Distance Between Center Terminal And Outside Terminal:     |  |  |  |  |  |
| 0.156 inches  |  |  |  |  |  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |  |  |  |  |  |
| 105.0 single section  |  |  |  |  |  |
| Power Dissipation Rating Per Section In Watts:                              |  |  |  |  |  |
| 0.1 free air single section   |  |  |  |  |  |
| Resistance Tolerance Per Section In Percent:                                |  |  |  |  |  |
| -30.0 to 30.0 single section  |  |  |  |  |  |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:         |  |  |  |  |  |
| 70.0 single section   |  |  |  |  |  |
| Standard Taper Curve Per Section:   |  |  |  |  |  |
| A single section  |  |  |  |  |  |
| Terminal Type And Quantity:   |  |  |  |  |  |
| 3 pin   |  |  |  |  |  |
| Shelf Life:   |  |  |  |  |  |
| N/a   |  |  |  |  |  |

## NSN 5905-00-233-4490

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



|    | • - |      |         |   |
|----|-----|------|---------|---|
| In | ıŧ  | ( )t | Measure | • |
|    |     |      |         |   |

--

Demilitarization:

No

Fiig:

A002a0