NSN 5905-00-233-5766

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-233-5766

-200.0/+200.0 Electrical Resistance: 33.000 ohms Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established
Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
-2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
-55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Encapsulated Terminal Type: Wire lead Reliability Indicator:
Terminal Type: Wire lead Reliability Indicator:
Wire lead Reliability Indicator:
Reliability Indicator:
Established
Lotabiloticu
Reliability Failure Rate Level In Percent:
1.000
Body Diameter:
0.318 inches
Body Length:
0.688 inches
Power Dissipation Rating In Watts:
2.000 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-milr39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A001a0