NSN 5905-00-234-0159

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-234-0159 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.060 inches **Terminal Length:** 0.200 inches **Overall Height:** 0.560 inches **Overall Width:** 0.280 inches **Mounting Hole Diameter:** 0.088 inches **Shaft Diameter:** 0.100 inches **Shaft Length:** 0.060 inches **Body Length:** 1.000 inches **Body Width:** 0.280 inches **Body Height:** 0.360 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 8.00 inch-ounces **Center To Center Distance Between Terminals:** 0.500 inches

Lateral Distance Between Mounting Hole Centers:

0.830 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal and unthreaded hole

NSN 5905-00-234-0159

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
5400.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0