

View Online at <https://aerobasegroup.com/nsn/5905-00-234-7543>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

3.310 inches

Shaft Diameter:

0.2497 inches

Shaft Length:

0.440 inches

Mounting Bushing Length:

0.500 inches

Body Length:

2.750 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 5400.0 and 5404.0

Shaft End Play:

0.007 inches

Shaft Runout:

0.0005 inches

Lateral Runout:

0.003 inches

Pilot Diameter Runout:

0.0002 inches

Shaft Radial Play:

0.003 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 5400.0 and 5404.0

Function Conformity Tolerance Per Section:

-0.025/+0.025 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Power Dissipation Rating Per Section In Watts:

10.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-2.0/+2.0 ohms single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Tap Location From Ccw Terminal Per Section In Ohms:

500.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0