Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-234-7810

Section	Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

0.325 inches

Body Length:

0.276 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Center To Center Distance Between Terminals:

0.200 inches

Terminal Location:

Rear end

Mounting Method:

Terminal

Electrical Resistance Per Section:

500.0 ohms single section

Rotary Actuator Travel In Angular Deg:

320.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0