

View Online at <https://aerobasegroup.com/nsn/5905-00-235-7820>

Section Quantity:

1

Body Style:

Cylindrical studs mounted

Body Diameter:

3.000 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.531 inches

Body Length:

1.188 inches

Mounting Hole/stud Circle Diameter:

1.750 inches

Shaft Style:

Round, slotted

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

310.0

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Screw Thread Diameter:

0.164 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

3

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

10.000 kilohms single section

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

155.0 single section

Rotary Actuator Travel In Angular Deg:

310.0

Function Conformity Tolerance Per Section:

-0.30/+0.30 single section

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-1.0/+1.0 degrees angular rotation single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

20.0 single section

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0