NSN 5905-00-235-8479

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-235-8479

Section Quantity:
1
Body Style:
Rectangular w/mounting hole/slot
Reliability Indicator:
Not established
Shaft Diameter:
0.075 inches
Shaft Length:
0.080 inches
Body Length:
0.540 inches
Body Width:
0.165 inches
Body Height:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Left adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
1.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-00-235-8479

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Test Data Document:

81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal	Type	And	Quantity	v:

3 pin

Specification Data:

81349-mil-r-22097/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0