Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-235-8520

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.594 inches

Body Diameter:

0.500 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.469 inches

Overall Diameter:

0.875 inches

Shaft Style:

Round, slotted

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0 and 28.0

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

275.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Maximum Stop Torque:

64.00 inch-ounces

Nonturn Device Location:

At one thirty oclock

Nonturn Device Radius:

0.245 inches

Mechanical Backlash In Deg Angular Rotation:

3.0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Switch Operating Position: Start of rotation Switch Contact Arrangement: Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear-bottom **Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 2.5 kilohms single section **Rotary Actuator Travel In Angular Deg:** 295.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Switch Current Type And Rating In Amps: 0.500 ac and 1.500 dc **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 5 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0