Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-236-2984

## Section Quantity:

1

Body Style:

Rectangular

### Reliability Indicator:

Not established

#### **Terminal Length:**

0.240 inches

#### Shaft Diameter:

0.070 inches

#### Shaft Length:

0.040 inches

#### Body Length:

0.500 inches

#### Body Width:

0.100 inches

# Body Height:

0.150 inches

# Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### Maximum Starting Torque:

2.00 inch-ounces

#### Maximum Running Torque:

2.00 inch-ounces

#### Center To Center Distance Between Terminals:

0.400 inches

#### **Terminal Location:**

Lower adjacent side single row

#### **Mounting Method:**

Terminal

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

3600.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.6 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

## **Actuator Travel Control Feature:**

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0