Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-236-7540

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## Body Diameter:

1.562 inches

## Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

## Mounting Bushing Length:

0.375 inches

## Body Length:

# 1.375 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

295.0

#### Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

## **Electrical Resistance Per Section:**

15.0 ohms single section

## Rotary Actuator Travel In Angular Deg:

295.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# NSN 5905-00-236-7540

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

25.0 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

### Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

#### Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A002a0