## NSN 5905-00-237-6176

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-237-6176 **Section Quantity:** 1 **Body Style:** Cylindrical hole/slot mounted **Overall Length:** 3.285 inches **Terminal Length:** 0.365 inches First Flat Length: 0.340 inches Flat Height: Between 0.339 inches and 0.349 inches **Body Diameter:** 6.810 inches **Shaft Diameter:** Between 0.373 inches and 0.376 inches **Shaft Length:** 0.875 inches **Body Length:** 2.410 inches **Overall Diameter:** 7.175 inches **Mounting Hole/stud Circle Diameter:** Between 2.360 inches and 2.390 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 20.0 **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** 

Threaded hole

**Electrical Resistance Per Section:** 

40.000 ohms single section

## NSN 5905-00-237-6176

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
315.0
Power Dissipation Rating Per Section In Watts:
300.0 heat sink single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0