## NSN 5905-00-238-3422

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-238-3422

| view Offilite at https://aerobasegroup.com/histi/0300-00-230-0422  |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
| -50.0 to 50.0  |
| Electrical Resistance:   |
| 121.000 ohms   |
| Resistance Tolerance In Percent:   |
| -1.000 to 1.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 125.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 175.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0 to 175.0   |
| Inclosure Method:  |
| Hermetically sealed  |
| Terminal Type:   |
| Wire lead  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.001  |
| Terminal Length:   |
| Between 1.000 inches and 1.625 inches  |
| Body Diameter:   |
| Between 0.157 inches and 0.250 inches  |
| Body Length:   |
| Between 0.531 inches and 0.656 inches  |
| Power Dissipation Rating In Watts:   |
| 0.250 free air   |
| Unpackaged Unit Weight:  |
| 0.84 grams   |
| Style Designator:  |
| Axial terminal each end  |
| Test Data Document:  |
| 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-r-55182/5 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |

No

Demilitarization:

## NSN 5905-00-238-3422

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0