Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-238-3837

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### First Flat Length:

1.562 inches

#### Flat Height:

0.344 inches

#### **Body Diameter:**

6.000 inches

#### Shaft Diameter:

0.375 inches

### Shaft Length:

### 2.000 inches

**Body Length:** 

### 2.375 inches

Shaft Style:

Round, flatted

### Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

320.0

### Screw Thread Diameter:

0.250 inches

### Screw Thread Series Designator:

Unc

### Screw Thready Qty Per Inch (tpi):

20.0

# **Mounting Facility Quantity:**

2

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Threaded hole

# **Electrical Resistance Per Section:**

500.0 ohms single section

# Rotary Actuator Travel In Angular Deg:

320.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

# NSN 5905-00-238-3837 Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

300.0 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Actuator Travel Control Feature:

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

### Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

#### Fiig:

A002a0