Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-238-5828

Section	Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.125 inches

**Body Length:** 

0.480 inches

**Body Width:** 

0.375 inches

Body Height:

0.236 inches

#### Actuator Type:

Flush drive with slot-hole

#### Center To Center Distance Between Terminals:

0.400 inches

#### **Terminal Location:**

Lower adjacent side two rows

#### Mounting Method:

Terminal

### Center To Center Distance Between Terminal Rows:

0.100 inches

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

### **Rotary Actuator Travel In Angular Deg:**

270.0

### Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 150.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

### **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

### Actuator Travel Control Feature:

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section



Standard Taper Curve Per Section:

A single section

### Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A002a0