

View Online at <https://aerobasegroup.com/nsn/5905-00-238-7085>

**Section Quantity:**

1

**Body Style:**

Rectangular bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

Between 1.433 inches and 1.563 inches

**Overall Height:**

Between 0.292 inches and 0.332 inches

**Overall Width:**

Between 0.292 inches and 0.332 inches

**Mounting Bushing Length:**

Between 0.158 inches and 0.218 inches

**Body Length:**

Between 1.040 inches and 1.080 inches

**Body Width:**

Between 0.292 inches and 0.332 inches

**Body Height:**

Between 0.292 inches and 0.332 inches

**Actuator Type:**

Flush drive with slot-hole

**Maximum Starting Torque:**

5.00 inch-ounces

**Screw Thread Diameter:**

0.216 inches

**Screw Thread Series Designator:**

Unf

**Screw Thread Qty Per Inch (tpi):**

28.0

**Terminal Location:**

Rear end

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

50.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

175.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-50.0 to 50.0 single section

**Power Dissipation Rating Per Section In Watts:**

9.75 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 wire loop

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0