NSN 5905-00-239-7582

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-239-7582 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Body Length:** 0.438 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 295.0 **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.245 inches **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Tab **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 250.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 295.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:**

A single section

Terminal Type And Quantity:

3 tab, solder lug

NSN 5905-00-239-7582

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0