# NSN 5905-00-240-2012

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-240-2012

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-50.0/+50.0

## **Electrical Resistance:**

100.000 kilohms

## **Resistance Tolerance In Percent:**

-1.000/+1.000

## Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+175.0

## **Inclosure Method:**

Hermetically sealed

#### **Terminal Type:**

Wire lead

## Reliability Indicator:

Established

# Reliability Failure Rate Level In Percent:

0.001

# Terminal Length:

Between 1.375 inches and 1.625 inches

# **Body Diameter:**

Between 0.078 inches and 0.140 inches

#### **Body Length:**

Between 0.204 inches and 0.281 inches

# **Power Dissipation Rating In Watts:**

0.125 free air

# Style Designator:

Axial terminal each end

# Test Data Document:

81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-prf-55182/1 government specification

# Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A001a0

NSN 5905-00-240-2012

Film Fixed Resistor - Page 2 of 2

Mil-std (military Standard):

Mil-prf-55182 spec.

