NSN 5905-00-240-3015

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-240-3015

Electrical Resistance: 10.000 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: I-dermetically sealed Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established
1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established
Ambient Tempurature In Deg Celsius At Full Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: Ambient Tempurature In Deg Celsius At Z
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established
55.0/+175.0 nclosure Method: Hermetically sealed Ferminal Type: Wire lead Reliability Indicator: Established
nclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established
Hermetically sealed Ferminal Type: Wire lead Reliability Indicator: Established
Ferminal Type: Wire lead Reliability Indicator: Established
Wire lead Reliability Indicator: Established
Reliability Indicator: Established
Established
Reliability Failure Rate Level In Percent:
tonability I alialo fato Lotol III I olooliti
0.001
Body Diameter:
0.125 inches
Body Length:
0.375 inches
Power Dissipation Rating In Watts:
0.125 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A001a0