## NSN 5905-00-240-7693

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-240-7693 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.172 inches **Shaft Diameter:** Between 0.058 inches and 0.098 inches **Shaft Length:** 0.045 inches **Body Length:** Between 0.490 inches and 0.510 inches **Body Width:** Between 0.180 inches and 0.230 inches **Body Height:** 0.540 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 7200.0 and 16200.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.195 inches and 0.205 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Lower adjacent side single row **Mounting Method: Terminal Features Provided:** 

Humidity proof

**Cubic Measure:** 

0.055 cubic inches

## NSN 5905-00-240-7693

**Terminal Type And Quantity:** 

81349-mil-r-22097/3 government specification

**Specification Data:** 

**Unit Of Measure:** 

**Demilitarization:** 

3 pin

N/a

No Fiig: A002a0

Shelf Life:

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 7200.0 and 16200.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.095 inches and 0.105 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0 to 250.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).