## NSN 5905-00-241-3005

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-241-3005

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length:
0.810 inches
Terminal Length:
0.150 inches
Overall Height:
0.460 inches
Overall Width:
0.160 inches
Shaft Diameter:
0.100 inches
Shaft Length:
0.060 inches
Body Length:
0.750 inches
Body Width:
0.160 inches
Body Height:
0.310 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
7200.0
Center To Center Distance Between Terminals:
0.500 inches
Fragility Factor:
Moderately delicate
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Features Provided:

Nonmetallic shaft and humidity proof

## NSN 5905-00-241-3005

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
200.0 ohms single section
Rotary Actuator Travel In Angular Deg:
7200.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A002a0