NSN 5905-00-241-3149

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-241-3149 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.314 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.689 inches **Overall Diameter:** 0.875 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Running Torque:** 0.50 inch-ounces **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Front end **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:**

5.0 kilohms single sectionRotary Actuator Travel In Angular Deg:300.0

NSN 5905-00-241-3149

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation	Rating Pe	r Section Ir	Watts:
-------------------	-----------	--------------	--------

12.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0