NSN 5905-00-242-7683

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-242-7683 **Section Quantity: Body Style:** Cylindrical tab/flange mounted **Reliability Indicator:** Not established **Terminal Length:** 0.219 inches **Body Diameter:** 1.250 inches **Mounting Hole Diameter:** 0.136 inches **Body Length:** 0.420 inches **Actuator Type:** Flush drive with slot-hole **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Unthreaded hole **Features Provided:** Grounded contact arm and nonmetallic shaft **Electrical Resistance Per Section:** 3.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5905-00-242-7683

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0