## NSN 5905-00-242-9244

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-242-9244

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.570 inches
Body Diameter:
0.515 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.660 inches
Mounting Bushing Length:
0.280 inches
Body Length:
0.660 inches
Overall Diameter:
0.515 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Maximum Starting Torque:
32.00 inch-ounces
Maximum Running Torque:
4.00 inch-ounces
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:

75.0 ohms single section

## NSN 5905-00-242-9244

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
7.5 free air single section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4002a0