Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-242-9765

view Online at https://aerobasegroup.com/nsi//300-00-242-9/03
Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.187 inches
Shaft Diameter:
0.062 inches
Shaft Length:
Between 0.040 inches and 0.060 inches
Body Length:
0.250 inches
Body Width:
0.156 inches
Body Height:
0.250 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Maximum Starting Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section



Power Dissipation Rating Per Section In Watts:

0.1 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

125.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0