## NSN 5905-00-243-7997

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-243-7997 **Section Quantity: Shaft Bearing Type:** Ball **Effective Electrical Rotation In Deg Angular Rotation:** 342.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Shaft End Play:** 0.00300 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.002 inches **Pilot Diameter Runout:** 0.00100 inches **Shaft Radial Play:** 0.001 inches **Terminal Location:** Radially positioned over less than half the circumference **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 5.000 percent, rated amperes c and better finish **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -1.00/+1.00 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Shelf Life: N/a

\_\_

**Unit Of Measure:** 

## NSN 5905-00-243-7997

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0