NSN 5905-00-244-4208

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-244-4208

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.9688 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
0.975 inches
Undercut Width:
0.0700 inches
Body Diameter:
1.080 inches
Shaft Diameter:
0.1248 inches
Shaft Length:
0.700 inches
Body Length:
0.590 inches
Mounting Lip Diameter:
1.0620 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
1.5 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.5 free air single section
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:

-2.0/+2.0 ohms single section

NSN 5905-00-244-4208

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance	Tolerance	Per Section	In Percent:
Nesisianice	i olei alice	rei Section	III Feiceill.

-10.0/+10.0 single section

Tap Location From Ccw Terminal Per Section In Ohms:

1500.0 single section

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0