NSN 5905-00-244-8078

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-244-8078 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.202 inches **Shaft Diameter:** 0.092 inches **Shaft Length:** 0.085 inches **Body Length:** 0.380 inches **Body Width:** 0.245 inches **Body Height:** 0.380 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** 0.210 inches **Terminal Location:** Left adjacent side two rows **Mounting Method: Terminal Center To Center Distance Between Terminal Rows:** 0.105 inches **Features Provided:**

Electrical Resistance Per Section: 5.0 kilohms single section

Nonmetallic shaft

NSN 5905-00-244-8078

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.105 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0