Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-246-1188

# Section Quantity:

1

Body Style:

Cylindrical

### Reliability Indicator:

Not established

### **Body Diameter:**

0.532 inches

#### **Body Length:**

0.179 inches

#### Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

275.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Tab

#### **Features Provided:**

Grounded contact arm

### **Electrical Resistance Per Section:**

20.0 kilohms single section

### Rotary Actuator Travel In Angular Deg:

294.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

### **Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-30.0 to 30.0 single section

### Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

## Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

2 tab, solder lug

### Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0