## NSN 5905-00-247-1474

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-247-1474 **Section Quantity: Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Shaft Style:** Round, slotted Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Double pole, single throw, normally open **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 100.000 kilohms single section **Power Dissipation Rating Per Section In Watts: Resistance Tolerance Per Section In Percent:** 

1.0 free air single section -10.0/+10.0 single section **Switch Current Type And Rating In Amps:** 2.000 ac/dc Shelf Life: N/a

## NSN 5905-00-247-1474

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	• -			
In	ıŧ	( )t	Measure	•

--

Demilitarization:

No

Fiig:

A002a0