## NSN 5905-00-247-2541

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-247-2541

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -0.100/-0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.438 inches Body Length: 0.906 inches Power Dissipation Rating in Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247asco304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	-1.0/+1.0
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Rediability Indicator: Not established Body Diameter: 0.438 inches Body Length: 0.300 free air Style Designator: Axial terminal each end Test Data Document: Story and Story	Electrical Resistance:
-0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.438 inches Body Length: 0.390 finches Power Dissipation Rating In Watts: 0.390 fire air Style Designator: Axial terminal each end Test Data Document: 30003-247-asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	6.650 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power:  25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: ++0.0/+60.0  Inclosure Method: Hermetically sealed  Terminal Type: Wire lead Reliability Indicator: Not established  Body Diameter: 0.438 inches  Body Length: 0.906 inches  Power Dissipation Rating In Watts: 0.300 free air  Style Designator: Axial terminal each end  Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Flig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.438 inches Body Length: 0.906 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.438 inches Body Length: 0.906 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.438 inches Body Length: 0.906 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.438 inches Body Length: 0.906 inches Power Dissipation Rating in Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
+0.0/+60.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.438 inches Body Length: 0.996 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	125.0
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.438 inches Body Length: 0.906 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Hermetically sealed  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.438 inches  Body Length:  0.906 inches  Power Dissipation Rating In Watts:  0.300 free air  Style Designator:  Axial terminal each end  Test Data Document:  30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  — Demilitarization:  No  Fig:	+0.0/+60.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.438 inches  Body Length: 0.906 inches  Power Dissipation Rating In Watts: 0.300 free air  Style Designator:  Axial terminal each end  Test Data Document:  30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.438 inches  Body Length: 0.906 inches  Power Dissipation Rating In Watts: 0.300 free air  Style Designator:  Axial terminal each end  Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Hermetically sealed
Reliability Indicator:  Not established  Body Diameter: 0.438 inches  Body Length: 0.906 inches  Power Dissipation Rating In Watts: 0.300 free air  Style Designator:  Axial terminal each end  Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Terminal Type:
Note established  Body Diameter:  0.438 inches  Body Length: 0.906 inches  Power Dissipation Rating In Watts: 0.300 free air  Style Designator:  Axial terminal each end  Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Wire lead
Body Diameter:  0.438 inches  Body Length: 0.906 inches  Power Dissipation Rating In Watts: 0.300 free air  Style Designator: Axial terminal each end  Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fig:	Reliability Indicator:
Body Length:  0.906 inches  Power Dissipation Rating In Watts: 0.300 free air  Style Designator: Axial terminal each end  Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig:	Not established
Body Length:  0.906 inches  Power Dissipation Rating In Watts:  0.300 free air  Style Designator:  Axial terminal each end  Test Data Document:  30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Diameter:
0.906 inches  Power Dissipation Rating In Watts: 0.300 free air  Style Designator:  Axial terminal each end  Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.438 inches
Power Dissipation Rating In Watts:  0.300 free air  Style Designator: Axial terminal each end  Test Data Document:  30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Body Length:
O.300 free air  Style Designator: Axial terminal each end  Test Data Document: 30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.906 inches
Style Designator:  Axial terminal each end  Test Data Document:  30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.300 free air
Test Data Document:  30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Style Designator:
30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Axial terminal each end
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	30003-247asc0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
N/a Unit Of Measure: Demilitarization: No Fiig:	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
700100	A001a0