Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-247-8594

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 0.780 inches and 0.840 inches **Terminal Length:** Between 0.185 inches and 0.255 inches **Overall Height:** Between 0.520 inches and 0.600 inches **Overall Width:** Between 0.270 inches and 0.290 inches Shaft Diameter: Between 0.090 inches and 0.110 inches Shaft Length: Between 0.045 inches and 0.075 inches **Body Length:** Between 0.735 inches and 0.765 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.345 inches and 0.375 inches Shaft Style: Round, slotted **Contact Arm Electrical Off Position:** Fully ccw Actuator Type: Single shaft **Center To Center Distance Between Terminals:** Between 0.490 inches and 0.510 inches Lateral Distance Between Mounting Hole Centers: 0.419 inches **Terminal Location:** Lower adjacent side single row **Mounting Method:** Terminal **Electrical Resistance Per Section:** 200.0 kilohms single section Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.090 inches and 0.110 inches



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0 to 0.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0