

View Online at <https://aerobasegroup.com/nsn/5905-00-249-5550>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

4.297 inches

**Terminal Length:**

0.555 inches

**First Flat Length:**

1.500 inches

**Flat Height:**

Between 0.339 inches and 0.349 inches

**Body Diameter:**

8.090 inches

**Shaft Diameter:**

Between 0.373 inches and 0.376 inches

**Shaft Length:**

Between 1.953 inches and 2.047 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

2.250 inches

**Overall Diameter:**

8.645 inches

**Shaft Style:**

Round, flatted

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

160.00 inch-ounces

**Maximum Stop Torque:**

240.00 inch-ounces

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unc

**Screw Thready Qty Per Inch (tpi):**

20.0

**Mounting Facility Quantity:**

2

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Threaded hole

**Electrical Resistance Per Section:**

150.000 ohms single section

**Rotary Actuator Travel In Angular Deg:**

Between 320.0 and 330.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

390.0 single section

**Power Dissipation Rating Per Section In Watts:**

500.0 heat sink single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

Two mtg holes spaced 180 deg. 1.500 inch radius

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0