NSN 5905-00-249-5558

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-249-5558 **Section Quantity:** First Flat Length: 2.000 inches Flat Height: 0.216 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 2.500 inches **Mounting Bushing Length:** 0.375 inches **Overall Diameter:** 1.156 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 100.000 kilohms single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

Unit Of Measure:

NSN 5905-00-249-5558

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	2 †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A002a0