NSN 5905-00-249-7925

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-249-7925 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Body Diameter:** 1.060 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.440 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 500.000 ohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

--

Unit Of Measure:

NSN 5905-00-249-7925

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



D	:1:4.	-:-	-4:-	
Dem	HIT	arız	atıc	on:

No

Fiig:

A002a0