Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-250-2283

## Section Quantity:

1

**Body Style:** 

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Overall Length:**

3.952 inches

#### First Flat Length:

0.766 inches

#### Flat Height:

0.344 inches

#### Body Diameter:

10.090 inches

#### Shaft Diameter:

0.375 inches

#### \_\_\_\_

Shaft Length:

0.922 inches

## Mounting Bushing Length:

0.375 inches

#### Body Length:

3.030 inches

#### **Overall Diameter:**

10.675 inches

#### Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

0.33

#### Maximum Starting Torque:

160.00 inch-ounces

#### Maximum Running Torque:

16.00 inch-ounces

#### Maximum Stop Torque:

240.00 inch-ounces

## Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unc

# Screw Thready Qty Per Inch (tpi):

20.0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Mounting Facility Quantity:** 

2

Terminal Location:

Radially positioned over less than half the circumference

**Mounting Method:** 

Threaded hole

**Electrical Resistance Per Section:** 

3.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

0.330

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

390.0 single section

Power Dissipation Rating Per Section In Watts:

750.0 heat sink single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

## **Test Data Document:**

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

3 tab, solder lug

**Specification Data:** 

81349-mil-r-22/13 government specification

Shelf Life:

N/a

Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A002a0