

View Online at https://aerobasegroup.com/nsn/5905-00-250-3661

### Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-10.0/+10.0

#### **Electrical Resistance:**

1.840 kilohms

**Resistance Tolerance In Percent:** 

#### -0.010/+0.010

Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

#### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

145.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

#### -65.0/+145.0

**Inclosure Method:** 

#### Encapsulated

**Terminal Type:** 

#### Wire lead

Reliability Indicator:

## Established

Reliability Failure Rate Level In Percent:

0.010

#### **Terminal Length:**

1.500 inches

#### Body Diameter:

0.250 inches

#### Body Length:

0.344 inches

#### **Power Dissipation Rating In Watts:**

0.125 free air

#### **Unpackaged Unit Weight:**

1.500 grams

#### Style Designator:

Axial terminal each end

#### Test Data Document:

81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-r-39005/5 government specification

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 5905-00-250-3661

Noninductive Wire Wound Fixed Resistor - Page 2 of 2

Fiig: A001a0

