Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-250-5019

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# **Reliability Indicator:**

Not established

#### **Overall Length:**

1.308 inches

#### **Overall Height:**

0.320 inches

#### **Overall Width:**

0.190 inches

#### Mounting Hole Diameter:

0.093 inches

#### Shaft Diameter:

# 0.115 inches

Shaft Length:

### 0.058 inches

Body Length:

# 1.250 inches

Body Width:

#### 0.190 inches

**Body Height:** 

#### 0.320 inches

Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Maximum Starting Torque:

5.00 inch-ounces

## Lateral Distance Between Mounting Hole Centers:

1.000 inches

## **Mounting Facility Quantity:**

2

# Terminal Location:

Rear end

# Mounting Method:

Unthreaded hole

# **Electrical Resistance Per Section:**

200.0 ohms single section

# Rotary Actuator Travel In Angular Deg:

7920.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0