NSN 5905-00-250-5755

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-250-5755

Electrical Resistance: 519.000 ohms Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Irempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ireminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.0001 Body Diameter: 1.0109 inches Body Length: 1.0250 inches Power Dissipation Rating In Watts:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 3ody Diameter: 0.109 inches 3ody Length: 0.250 inches Power Dissipation Rating In Watts:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
2.001 Body Diameter: 2.109 inches Body Length: 2.250 inches Power Dissipation Rating In Watts:
Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts:
Body Length: 0.250 inches Power Dissipation Rating In Watts:
2.250 inches Power Dissipation Rating In Watts:
Power Dissipation Rating In Watts:
).100 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A001a0