## NSN 5905-00-250-7987

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-250-7987 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.5620 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.562 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.750 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.625 inches **Body Length:** 0.990 inches **Mounting Lip Diameter:** 1.7500 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Shaft Runout:** 0.001 inches

Lateral Runout: 0.005 inches

## NSN 5905-00-250-7987

No Fiig:

Precision Wire Wound Variable Resistor - Page 2 of 2



Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.0 kilohms all sections
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
5.4 2nd section and 10.8 2nd section and 21.6 2nd section and 54.0 2nd section and 118.0 2nd section and 129.6 2nd section and 180.0
2nd section and 185.4 2nd section and 190.8 2nd section and 201.6 2nd section and 234.0 2nd section and 298.8 2nd section and 309.6
2nd section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
0.25/+0.25 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
3.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
9 1st section
Гар Location Tolerance Per Section:
0.5/+0.5 degrees angular rotation all sections
Resistance Tolerance Per Section In Percent:
10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Terminal Type And Quantity:
28 turret
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization: