NSN 5905-00-250-9353

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-250-9353 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Overall Length:** 1.320 inches **Terminal Length:** 11.500 inches **Overall Height:** 0.300 inches **Overall Width:** 0.180 inches **Mounting Hole Diameter:** 0.088 inches **Shaft Diameter:** 0.110 inches **Shaft Length:** 0.070 inches **Body Length:** 1.250 inches **Body Width:** 0.180 inches **Body Height:** 0.300 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 5.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:**

5.000 kilohms single sectionRotary Actuator Travel In Angular Deg:7920.0

NSN 5905-00-250-9353

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 180.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -0.7 to 0.7 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**