## NSN 5905-00-251-9073

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-251-9073

View Online at https://aerobasegroup.com/nsn/5905-00-251-90
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 2.204 inches and 2.296 inches
First Flat Length:
Between 0.328 inches and 0.358 inches
Flat Height:
Between 0.211 inches and 0.221 inches
Body Diameter:
Between 1.547 inches and 1.577 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
Between 0.844 inches and 0.906 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Between 1.360 inches and 1.390 inches
Overall Diameter:
1.719 inches
Shaft Style:
Round, flatted
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 275.0 and 305.0
Maximum Starting Torque:
40.00 inch-ounces
Maximum Stop Torque:
240.00 inch-ounces
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
Between 0.502 inches and 0.522 inches
Screw Thread Diameter:

0.375 inches

## NSN 5905-00-251-9073

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
350.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 275.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
10.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A002a0