Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-251-9098

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### **Overall Length:**

2.026 inches

#### **Body Diameter:**

1.312 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

#### Shaft Length:

Between 1.344 inches and 1.406 inches

#### Mounting Bushing Length:

0.250 inches

#### **Body Length:**

0.620 inches

#### **Overall Diameter:**

1.718 inches

#### Shaft Style:

Round

#### Actuator Type:

Single shaft

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

### **Terminal Location:**

Radially positioned over less than half the circumference

### **Mounting Method:**

Standard bushing

### **Electrical Resistance Per Section:**

500.0 kilohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# Fixed Tap Quantity Per Section:

1 single section

### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

### Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0