Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-252-4090

## Section Quantity:

2

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

2.440 inches

#### Body Diameter:

1.280 inches

Shaft Diameter:

0.250 inches

Shaft Length:

Between 0.810 inches and 1.190 inches

#### Mounting Bushing Length:

0.380 inches

# Body Length:

1.250 inches

# Body Inside Diameter:

0.125 inches

## **Overall Diameter:**

1.280 inches

## Shaft Style:

Round, hollowed

#### Actuator Type:

Dual concentric

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# Center To Center Distance Between Terminal Rows:

0.100 inches

# **Features Provided:**

Nonmetallic shaft

# **Electrical Resistance Per Section:**

200.0 ohms 2nd section

# NSN 5905-00-252-4090

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

#### **Power Dissipation Rating Per Section In Watts:**

5.0 free air 2nd section

## **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 all sections

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Standard Taper Curve Per Section:

A all sections

#### **Terminal Type And Quantity:**

2 wire lead

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

### Fiig:

A002a0