

View Online at <https://aerobasegroup.com/nsn/5905-00-252-4221>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

0.875 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.566 inches

**Mounting Bushing Length:**

0.312 inches

**Body Length:**

0.678 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

1800.0

**Maximum Starting Torque:**

0.60 inch-ounces

**Maximum Running Torque:**

0.60 inch-ounces

**Shaft End Play:**

0.005 inches

**Shaft Runout:**

0.002 inches

**Shaft Radial Play:**

0.002 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

50.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

1800.0

**Function Conformity Tolerance Per Section:**

-0.30/+0.30 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.5 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0