Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-252-6445

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.938 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

3.000 inches

#### Mounting Bushing Length:

0.375 inches

#### Body Length:

## 0.516 inches

Shaft Style:

Round

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

280.0

## Nonturn Device Location:

At 3 oclock and at 9 oclock

## Nonturn Device Radius:

0.438 inches

#### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

3.000 kilohms single section

# Rotary Actuator Travel In Angular Deg:

300.0

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section



**Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0