NSN 5905-00-252-6460

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-252-6460 **Section Quantity:** 2 **Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established First Flat Length: 0.500 inches Flat Height: 0.216 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.875 inches **Body Width:** 0.937 inches **Body Height:** 1.125 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.437 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing

Electrical Resistance Per Section: 250.000 kilohms all sections

NSN 5905-00-252-6460

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.2 free air all sections
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0