

View Online at <https://aerobasegroup.com/nsn/5905-00-252-6463>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.938 inches

Shaft Diameter:

0.250 inches

Shaft Length:

3.000 inches

Body Length:

1.109 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

280.0

Nonturn Device Location:

At 3 oclock and at 9 oclock

Nonturn Device Radius:

0.438 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.0 megohms 2nd section

Rotary Actuator Travel In Angular Deg:

300.0

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 all sections

Actuator Travel Control Feature:

Stops

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0