NSN 5905-00-255-2440

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-255-2440

Section Quantity:
1
Reliability Indicator:
Not established
First Flat Length:
0.406 inches
Flat Height:
0.216 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.844 inches
Mounting Bushing Length:
0.375 inches
Shaft Style:
Round, flatted
Shaft Bearing Type:
Bearing
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
25.000 kilohms single section
Function Conformity Per Section:

Single section independent linearity

NSN 5905-00-255-2440

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section in Percent:
-20.0 to 20.0 single section
Switch Current Type And Rating In Amps:
3.000 ac/dc
Standard Taper Curve Per Section:
X single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0